


Double Bolt Clamps

Features:

- inner surface has dual gripping ridges
- bolt lugs are reinforced to prevent bending out of alignment
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance. 
- measure hose OD accurately before ordering clamps
- Consult Dixon™ when using double bolt clamps on helical wire hose.



without saddles



with saddles

Hose OD		Plated Iron		Opt Qty	Torque in ft. lbs.
from	to	Part #	Price/E		
1-8/64"	1-12/64"	J48	\$7.45	100	15
1-12/64"	1-24/64"	J49	9.00	50	21
1-28/64"	1-34/64"	JX49	12.35	25	21
1-40/64"	1-52/64"	DL14	13.45	25	40
1-48/64"	2-3/64"	DL20	13.25	25	27
2-7/64"	2-19/64"	DL24¹	12.70	25	27
2-20/64"	2-40/64"	DL32¹	13.70	25	40
2-32/64"	2-48/64"	DL275	17.40	25	40
2-48/64"	3-4/64"	DL306	20.15	20	60
3-4/64"	3-24/64"	DL328	21.30	20	60
3-16/64"	3-32/64"	DL350	20.50	20	60


¹ investment cast carbon steel

Hose OD		Plated Iron		Opt Qty	Torque in ft. lbs.
from	to	Part #	Price/E		
3-32/64"	3-52/64"	400	\$21.00	25	40
3-50/64"	4-4/64"	431	25.10	20	40
4-2/64"	4-18/64"	463	22.95	20	40
4-16/64"	4-60/64"	525	26.70	10	60
4-32/64"	5-16/64"	550	29.00	10	60
5-8/64"	5-44/64"	600	31.55	10	60
5-44/64"	5-60/64"	639	35.15	10	60
5-60/64"	6-32/64"	675	34.15	10	60
6-32/64"	7-36/64"	769	39.25	10	60
7-44/64"	8-12/64"	818	55.50	5	125
8-16/64"	8-56/64"	875	54.90	5	125
8-60/64"	9-56/64"	988	65.60	5	125
9-60/64"	11-24/64"	1125	99.00	5	125
11-12/64"	13"	1275	110.20	3	125
12-12/64"	14"	1360	180.25	2	200
13-12/64"	15"	1450	178.70	2	200
15-4/64"	17-32/64"	1700	208.10	2	260

K

Single Bolt Clamps

Features:

- measure hose OD accurately before ordering clamps
- Torque values for clamps are based on dry bolts.
- The use of lubricant on bolts will adversely effect clamp performance. 



Hose OD		Plated Iron		Torque in ft. lbs.
from	to	Part #	Price/E	
56/64"	1"	2	\$19.25	6
62/64"	1-8/64"	3	20.40	6
1-4/64"	1-12/64"	4	21.00	6
1-10/64"	1-16/64"	5	19.40	6
1-16/64"	1-24/64"	6	20.20	6
1-22/64"	1-28/64"	7	21.00	6
1-28/64"	1-36/64"	8	25.75	6
1-34/64"	1-44/64"	9	21.50	6
1-42/64"	1-48/64"	10	21.00	6
1-48/64"	1-56/64"	11	24.00	6
1-56/64"	2-2/64"	12	22.60	6
2"	2-8/64"	13	24.60	12
2-8/64"	2-18/64"	14	26.15	12
2-16/64"	2-26/64"	15	38.80	12

Hose OD		Plated Iron		Torque in ft. lbs.
from	to	Part #	Price/E	
2-24/64"	2-32/64"	16	\$24.20	12
2-32/64"	2-40/64"	17	23.60	12
2-40/64"	2-56/64"	18	29.50	12
2-56/64"	3-4/64"	19	28.25	12
3-4/64"	3-16/64"	20	27.70	12
3-16/64"	3-28/64"	21	31.75	12
3-28/64"	3-40/64"	22	29.50	21
3-40/64"	3-52/64"	23	41.00	21
3-52/64"	4-8/64"	24	37.90	21
4-8/64"	4-20/64"	25	38.45	21
4-16/64"	4-32/64"	26	39.50	21
4-28/64"	4-40/64"	27	46.70	21
4-40/64"	4-56/64"	X27	41.00	21
4-56/64"	5-16/64"	28	45.60	21