Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

LEAD FREE*

Series LF27

V-Pattern Lead Free* Bronze Threaded Strainers

Sizes: 1/8" - 1/2"

Series LF27 V-Pattern Lead Free* cast copper silicon alloy strainers are designed to protect system components from dirt, rust and other damaging debris in the piping system. This series is ideal for beverage dispensers, ice cube machines, dental equipment, instrument control systems and similar applications. The LF27 features Lead Free* construction to comply with Lead Free* installation requirements.

Features

- Lead Free* cast copper silicon alloy body
- V-pattern
- Lead Free* Brass retainer cap with gasket
- Threaded end connections

Pressure - Temperature

Maximum Working Pressure: 250psi (17.2 bar) CWP

Specifications

A V-pattern Lead Free* cast copper silicon alloy strainer to be installed as indicated on the plans. The strainer must have a Lead Free* brass retainer cap with gasket and threaded end connections. Strainer shall be rated to 250psi (17.2 bar) CWP. Strainer shall be a Watts Series LF27.

Materials

Body: Lead Free* Cast copper silicon alloy Retainer Cap: Lead Free* Brass with Gasket

Screen: Stainless Steel

Performance Data

SIZE	PRESSURE DROP ACROSS VALVE									
	psi	kPa	psi	kPa	psi	kPa	psi	kPa	psi	kPa
	2	14	4	28	6	41	8	55	10	69
in.	gpm	lpm	gpm	lpm	gpm	lpm	gpm	lpm	gpm	lpm
1/8	1.5	5.7	2.5	9.5	3.0	11.4	3.5	13.3	4.0	15.2
1/4	3.0	11.4	3.5	13.3	4.5	17.1	5.0	19.0	6.0	22.8
3/8	5.0	19.0	7.0	26.6	8.0	30.4	10.0	38.0	11.0	41.8
1/2	10.0	38.0	12.0	45.6	14.0	53.2	15.0	57.0	16.0	60.8



LF27

**Screen Options

304 Stainless Steel Wire Mesh Liners:

1/8": #40, #60, #80, #100


3/8": #24, #30, #40, #60 #80, #100, 1/4": #24, #30, #40, #60 #80, #100,

1/2": #24, #40, #60, #100

Consult factory for ordering codes

Dimensions - Weights

SIZE		DIMEN	ISIONS	WEI	GHT	SCREEN	
	P	4	В				**Std.Mesh
in.	in.	mm	in.	mm	lbs.	kgs	
1/8	13/4	44	17/16	37	0.38	0.17	#40
1/4	21/16	52	111/16	43	0.62	0.28	#30
3/8	21/2	64	23/16	56	0.75	0.34	#24
1/2	23/4	70	25/8	67	1.00	0.45	#24



NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

NOTICE

Inquire with governing authorities for local installation requirements

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.



USA: T: (978) 689-6066 • F: (978) 975-8350 • Watts.com **Canada:** T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca **Latin America:** T: (52) 81-1001-8600 • Watts.com

ES-LF27 1913 © 2019 Watts